







| CAPACITIES | | |
|--------------------------------------|------------------------------|--------------------|
| Snow Tank | | |
| Actual Volume | 2.83 m³ | 100 cu. ft. |
| Compacted | 3.54 m³ | 125 cu. ft. |
| Water | | |
| Ice Making | 738 L | 195 gal. |
| Wash Water | 310 L | 82 gal. |
| Total | 1048 L | 277 gal. |
| Hydraulic Oil | 60.6 L | 16 gal. |
| POWERTRAIN | | |
| Four-Wheel Drive | | |
| Motors | | |
| Electric Hydraulic Pump Motor | 8.2 kW | 11 HP |
| Electric Traction Motor | 17.9 kW | 24 HP |
| Battery ✓ Lead Acid or ⊕ Lithium-ion | *Accommodates a Variety of I | Battery Capacities |
| Axles | | |
| Front | 2903 kg | 6400 lb |
| Rear | 2903 kg | 6400 lb |

| DIMENSIONS | | | | | | | |
|-------------------------------------|------------------|----------|---------|----------|----------|---------|--|
| Overall | L | W | Н | L | W | Н | |
| Snow Tank Down | 4.04 m | 2.13 m | 2.26 m | 159 in. | 84 in. | 89 in. | |
| Snow Tank Up | 5.03 m | 2.13 m | 3.73 m | 198 in. | 84 in. | 147 in. | |
| Shaving Blade | L | W | Н | L | W | Н | |
| 195.6 cm 77 in. Blade | 195.6 cm | 12.7 cm | 1.27 cm | 77 in. | 5 in. | 0.5 in. | |
| Clearance | | | | | | | |
| Minimum Operator Height Clearance | | 248.9 cm | | | 98 in. | | |
| Snow Pit Clearance | ow Pit Clearance | | | 125.7 cm | | | |
| Conveyor System | | | | | | | |
| Horizontal Auger Diameter | | 25.4 cm | | | 10 in. | | |
| Vertical Auger Diameter | | 25.4 cm | | | 10 in. | | |
| Manueverability | | | | | | | |
| Wheelbase | | | 1.96 m | | | 77 in. | |
| Wheel Track | | 1.37 m | | | 54 in. | | |
| Turning Radius at Conditioner | | 4.87 m | | | 16 ft. | | |
| Weight | | | | | | | |
| Empty with Lead Acid batt | tery | | 4423 kg | | | 9750 lb | |
| With Water with Lead Acid battery | | 5148 kg | | | 11350 lb | | |
| Empty with Lithium-ion battery | | 3311 kg | | | 7300 lb | | |
| With Water with Lithium-ion battery | | 4037 kg | | | 8900 lb | | |



✓ Standard ⊕ Option



FastICE® Ice Making System

Create superior ice with a computer controlled pump for an even and accurate fine mist water application. *optional equipment



Level-Ice® Laser Leveling System

Automated precision blade control provides consistently level ice and significant savings of energy, water and time. *optional equipment



Zamboni Connect™ System

Monitor consumption and optimize performance with predictive insight and resource management. *optional equipment



STANDARD FEATURES

2 Year Warranty

400 Micron Wash Water Deep Filter Bag

Aluminum Alloy Wheels

Battery: Lead Acid

Battery Charger: Microprocessor

Controlled

Brushless AC Motors

Chassis: Strong All Welded Steel Tubing

Conditioner Safety Guards

Dependable Sevcon® Gen4 Solid State

Controls

Digital Training and Reference Materials

Familiar Automobile-Style Foot Controls

Four-Wheel Drive

Guide Wheel

High Quality 9 Micron Filter

High Speed Vertical Auger

Hydraulic Oil Level Sight Gauge

LED Headlights and Tail lights

On-Dash Diagnostics

Parking Brake

Power Steering

Premium Polyester Felt Spreader Towel

Replaceable Poly Conditioner Side Plates

Rugged Dana Spicer® Axles

Rust-Free Poly Ice Making Water Tank

Snow Tank Safety Stand

Spare Tire and Wheel

Stainless Steel Hardware

Steering Wheel Spinner Knob

Touch Up Paint Kit

Tungsten Carbide Studded Tires

Variable Speed Electric Hydraulic Pump

Motor

Wide Spectrum of Premium Automotive

Paint Colors

OPTIONS

Advanced Water System (AWS™)

Automatic Snow Breaker

Back Up Alarm

Battery: Lithium-ion

Blade Change System

Cab Enclosure

Conditioner: 96" Blade

Conditioner: Galvanized

Electric Water Level Gauge

FastICE® Ice Making System

IceCaps® Wheel Advertising System

Heated Ergonomic Comfort Design Seat

Armrest

Seatbelt

Integrated Auger Washout System

Level-Ice®

Low Guide Wheel

Seat Belt

Snow Melting Kit

Snow Tank Dump Height Restriction

Snow Tank Light

Stainless Steel Water Distribution Pipe

Tire Wash System

Wash Water to Ice Making Water Transfer

Wash Water System with Poly Tank

Water Level Sight Gauge

Zamboni Power Brush[™] Board Brush

System

Zamboni Connect™ System

