







CAPACITIES					
Snow Tank					
Actual Volume	3.0 m ³	106 cu. ft.			
Compacted	3.74 m ³	132 cu. ft.			
Water					
Ice Making	757 L	200 gal.			
Wash Water	227 L	60 gal.			
Total	984 L	260 gal.			
Hydraulic Oil	91 L	24 gal.			
POWERTRAIN					
Four-Wheel Drive					
Motors					
AC Hydraulic Pump Motor	8.2 kW	11 HP			
AC Traction Motor	17.9 kW	24 HP			
Battery Lead Acid or Lithium-ion 	*Accommodates a Variety of Battery Capacities				
Axles					
Front	2717 kg	5990 lb			
Rear	4159 kg	9170 lb			

Standard 🕀 Option

ZAMBO

DIMENSIONS								
Overall	L	W	Н	L	W	н		
Snow Tank Down	4.04 m	2.13 m	2.26 m	159 in.	84 in.	89 in.		
Snow Tank Up	4.88 m	2.13 m	3.13 m	192 in.	84 in.	123 in.		
Shaving Blade	L	W	н	L	W	н		
195.6 cm 77 in. Blade	195.6 cm	12.7 cm	1.27 cm	77 in.	5 in.	0.5 in.		
Clearance								
Minimum Operator Height Clearance		243.8 cm			96 in.			
Snow Pit Clearance		99.06 cm			39 in.			
Conveyor System								
Horizontal Auger Diameter		25.4 cm			10 in.			
Vertical Auger Diameter		25.4 cm			10 in.			
Manueverability								
Wheelbase		1.96 m			77 in.			
Wheel Track		1.50 m			59 in.			
Turning Radius at Conditioner		4.83 m			15 ft. 10 in.			
Weight								
Empty with Lead Acid battery		4853 kg			10700 lb			
with Water with Lead Acid battery		5670 kg			12500 lb			
Empty with Lithium-ion battery		3402kg			7500 lb			
with Water with Lithium-ion battery		4220kg			9300 lb			

*Varies by region/market. Contact Zamboni or your Zamboni Authorized Distributor for details. Some features described or shown may be optional at extra cost and prices, colors, materials, specifications and models are subject to change. Some options are required in combination with other options. ZAMBONI and the configuration of the Zamboni® ice resurfacing machine are registered trademarks of Frank J. Zamboni & Co., Inc. © Zamboni 2022 Rev 12/2022



Automatic Snow Breaker

Eliminates the need for manual control of the snow breaker by the machine operator.



Zamboni Power Brush™ Wider brush path reaches higher on the dasher board kick plate for superior cleaning power.



Ergonomic Seat

Designed with the operator in mind, our premium seat has optimal adjustability. *optional equipment

STANDARD FEATURES

2 Year Warranty 400 Micron Wash Water Deep Filter Bag Aluminum Alloy Wheels Automatic Snow Breaker Battery: Lead Acid Battery Charger: Microprocessor Controlled Brushless AC Motors Chassis: Strong All Welded Steel Tubing Conditioner Safety Guards Dependable Sevcon[®] Gen4 Controls Digital Training and Reference Materials **Dual Water Fill Pipes** Electric Water Level Gauge Four-Wheel Drive Guide Wheel High Quality 9 Micron Filter High Speed Vertical Auger Hydraulic Oil Level Sight Gauge LED Headlights and Tail lights

On-Dash Diagnostics Operator Area Storage Bins Parking Brake Power Steering Premium Polyester Felt Spreader Towel Replaceable Poly Conditioner Side Plate Rugged Dana Spicer[®] Axles Rust-Free Poly Ice Making Water Tank Rust-Free Poly Wash Water Tank Single Point Battery Watering System Snow Tank Maintenance Support Spare Tire and Wheel Stainless Steel Water Distribution Pipe Steering Wheel Spinner Knob Touch-Up Paint Kit Tungsten Carbide Studded Tires Wide Spectrum of Premium Automotive Paint Colors Zamboni Power Brush[™] Board Brush System

OPTIONS

Advanced Water System (AWS[™]) Back Up Alarm Battery: Lithium-ion Blade Change System Board Spray Conditioner: 96″ Blade Conditioner: Galvanized FastICE[®] Ice Making System Heated Ergonomic Comfort Design Seat • Armrest • Seatbelt IceCaps[®] Wheel Advertising System Level-Ice[™] Rotating Beacon Light

Rotating Beacon Light Snow Tank Light Tire Wash System Wash Water to Ice Making Water Transfer Zamboni Connect[™] System

MODEL 650 Electric

ZAMBONI

Some features described or shown may be optional at extra cost and prices, colors, materials, specifications and models are subject to change. Some options are required in combination with other options. ZAMBONI and the configuration of the Zamboni® ice resurfacing machine are registered trademarks of Frank J. Zamboni & Co., Inc. © Zamboni 2022 Rev 12/2022