





MODEL 700

| CAPACITIES | | | | | |
|------------------|--|-------------|--|--|--|
| Snow Tank | | | | | |
| Actual Volume | 3.54 m ³ | 125 cu. ft. | | | |
| Compacted | 4.53 m ³ | 160 cu. ft. | | | |
| Excess Water | 662 L | 175 gal. | | | |
| Water | | | | | |
| Ice Making | 1514 L | 400 gal. | | | |
| Wash Water | 416 L | 110 gal. | | | |
| Total | 1930 L | 510 gal. | | | |
| Hydraulic Oil | 125 L | 33 gal. | | | |
| POWERTRAIN | | | | | |
| Four-Wheel Drive | | | | | |
| Engine | GM® 4.3 L Six Cylinder Engine 75 kW / 100 HP at 2800 RPM | | | | |
| Transmission | Continuously variable hydrostatic pump and motor are axial-piston type. | | | | |
| Hydraulics | Double pump powers the vertical and horizontal augers. Hydraulic down pressure for optimal resurfacing results. | | | | |
| Axles | Rugged Dana Spicer [®] Model 70 Axles | | | | |
| Brakes | Full Hydrodynamic Braking | | | | |

| DIMENSIONS | | | | | | | |
|-----------------------------------|----------|----------|---------|---------|---------|----------|--|
| Overall | L | W | н | L | w | н | |
| Snow Tank Down | 4.04 m | 2.59 m | 2.44 m | 159 in. | 102 in. | 96 in. | |
| Snow Tank Up | 5.03 m | 2.59 m | 4.17 m | 198 in. | 102 in. | 164 in. | |
| Shaving Blade | L | W | н | L | W | н | |
| | 243.8 cm | 12.7 cm | 1.27 cm | 96 in. | 5 in. | 0.5 in. | |
| Clearance | | | | | | | |
| Minimum Operator Height Clearance | | 264.2 cm | | | 104 in. | | |
| Snow Pit Clearance | | 1.38 m | | | | 54.5 in. | |
| Conveyor System | | | | | | | |
| Horizontal Auger Diameter | | 25.4 cm | | | 10 in. | | |
| Vertical Auger Diameter | | 25.4 cm | | | | 10 in. | |
| Manueverability | | | | | | | |
| Wheelbase | | 1.96 m | | | 77 in. | | |
| Wheel Track | | 1.83 m | | | 72 in. | | |
| Turning Radius at Conditioner | | 6.1 m | | | 20 ft. | | |
| Weight | | | | | | | |
| Empty | | 4273 kg | | | | 9420 lb | |
| with Water | | 6214 kg | | | | 13700 lb | |





Galvanized Conditioner Durable galvanized steel provides a scratch-free finish with protection from rust. *optional equipment

STANDARD FEATURES

- 2 Year Warranty 400 Micron Wash Water Deep Filter Bag Chassis: Strong All Welded Steel Tubing Chrome Wheels Conditioner Safety Guards Digital Training and Reference Materials Engine: EPA and CARB Certified Familiar Automobile-Style Foot Controls Four-Wheel Drive Fuel Options: Gasoline, Propane Full Hydrodynamic Braking Galvanized Steel Ice Making Water Tank Guide Wheel Headlights and Tail Light (for Off Ice Travel) High Quality 9 and 10 Micron Filters High Speed Vertical Auger Hydraulic Oil Level Sight Gauge Load Sensing Engine Governor Multi-Function Display
- On-Dash Diagnostics Parking Brake Power Steering Replaceable Poly Conditioner Side Plates Rugged Dana Spicer® Axles Snow Tank Safety Stand Spare Tire and Wheel Stainless Steel Hardware Steering Wheel Spinner Knob Touch-Up Paint Kit Tungsten Carbide Studded Tires Under Seat Storage Wide Spectrum of Premium Automotive Paint Colors

Zamboni Power Brush™

power. *optional equipment

Wider brush path reaches higher on the

dasher board kick plate for superior cleaning

OPTIONS

*optional equipment

Automatic Snow Breaker

Eliminates the need for manual control of

the snow breaker by the machine operator.

Automatic Snow Breaker Back Up Alarm Cab Enclosure Conditioner: Galvanized Electric Water Level Gauge Hydraulic Oil Cooler Kit IceCaps® Wheel Advertising System Low Fuel Light Snow Melting Kit Snow Tank Dump Height Restriction Snow Tank Dump Height Restriction Snow Tank Light Tire Wash System Wash Water to Ice Making Water Transfer Zamboni Power Brush™ Board Brush System

MODEL 700

ZAMBONI

Some features described or shown may be optional at extra cost and prices, colors, materials, specifications and models are subject to change. Some options are required in combination with other options. ZAMBONI and the configuration of the Zamboni® ice resurfacing machine are registered trademarks of Frank J. Zamboni & Co., Inc. © Zamboni 2019 Rev 02/2019